



Guam solar frontier sf175 s

How much power does a SF PV module produce?

re: 25 °C, air mass 1.5, solar irradiance 1,000 W/m²). SF PV Module power output in actual operating conditions may vary. The amount of electrical direct current generated by SF PV modules is proportional to irradiance

Are sf145 & 170 modules RoHS compliant?

3.8 %. All modules are RoHS compliant and cadmium- and lead-free. Fewer production steps and raw materials also mean an industry-leading energy payback time of less than one year. SF145-170 modules are shipped at nominal power I_{mp} 1.80 A 1.85 A 1.88 A 1.91 A 1.93 A 1.95 A Standard Test Conditions (STC)

Can SF PV modules be disassembled?

ical specifications. 6.3 Module Handling instructions Do not disassemble or modify SF PV modules. This may result in an electric shock, fire or other accidents. Solar Frontier cannot be held responsible for any loss or damage caused by unauthorized disassembly, modification or misuse of SF PV modules. Do not

Can SF PV modules be used in a road transport system?

all necessary measures are taken to prevent accidents. The use of SF PV modules in applications that may endanger human lives is prohibited, including in air and road transport systems. SF modules must not be used for anything other than their express purpose. Solar Frontier strongly advises you to follow the instructions below in order

Are SF PV modules waterproof?

ation tools or installation area are exposed to water. Ensure that the connection parts between SF PV modules and power receiving devices are isolated and waterproof. Using SF PV modules with insufficient isolation and waterproofing could result in an electric shock, an electric leak or an accident. Keep the junction box and the module connection

Does Solar Frontier offer a warranty certificate for PV modules?

he proprietary information of Solar Frontier K.K. (SF). SF's Limited Warranty Certificate for PV modules will be voided if the instructions here within are not strictly observed. SF will not assume any liability for damage arising from improper use, wrong assembly, operation and maintenance. Solar Frontier reserves the right to make amendment

W/m² irradiance, air temperature 20 °C, wind speed 1 m/s and open circuit condition. Efficiency reduction of maximum power from an irradiance of 1,000 W/m² to 200 W/m² at 25 °C is ...

SF175-S Keine Mikrorisse Kein Cadmium, kein Blei Salz- und Sauerstoffnebel- Beständigkeit Kein PID Keine Hotspots Ammoniak- Beständigkeit Robuster Aufbau (Glas/Glas/Folie) ... Das Urheberrecht für

